

Noble Globetrotter I

General

Rig Type:	Drillship
Rig Design:	Globetrotter Class
Builder:	STX Shipbuilding & Huisman
Year Built / Upgraded:	2011
Classification:	ABS +A1, Drilling Unit, Ice Class IA, (E), +AMS, +ACCU, +DPS-3, RW
Flag:	Liberia
MODU Code:	1989

Ratings & Dimensions

Water Depth:	10,000 ft
Drilling Depth:	40,000 ft
Length:	620 ft
Breadth:	105 ft
Depth:	62 ft
Draft (Operating/ Transit):	39 ft / 39 ft
Moonpool:	89 ft x 37 ft
Variable Deck Load:	45,459 kips
Hook Load:	2,000 kips
Setback Capacity:	2,100 kips
Racking Capacity:	Twin Husiman Carousel storage for drill pipe, drill collars and casing up to 13 3/8 in OD
Quarters Capacity:	180

Capacities

Fuel:	21,564 bbls
Drill Water:	18,900 bbls
Liquid Mud:	15,000 bbls
Brine Storage:	5,000 bbls
Base Oil Storage:	5,000 bbls
Bulk Storage:	34,604 cu ft
Sack Storage:	10,000 sacks



Equipment

Derrick:	Huisman Multi Purpose Tower
Drawworks:	Huisman dual drum, heave compensated
Top Drive:	NOV TDS-1000
Rotary:	NOV D-605
Iron Roughneck:	NOV AR-5000
Motion Compensator:	Huisman Passive Heave Compensator, 39 ft stroke
Riser Tensioner / Stroke:	(8) Huisman Marine Riser Tensioners, 450 kips/ea; 50 ft stroke
Riser Details:	Shaffer Type FT-H
BOP:	NOV Shaffer NXT; 6 ram; 18-3/4 in x 15k psi w/ NOV Shaffer Spherical Slimline 18-3/4 in x 10k psi annular
LMRP:	(1) NOV Shaffer Spherical Slimline 18-3/4 in x 10 psi annular
Control System:	NOV Shaffer MUX System
Pipe Handling System:	(4) Huisman Column Rackers
Solids Control System:	(5) Brandt LCM-3D/CS, (1) Brandt Mud Cleaner LCM-3D/CS
Diverter:	NOV Shaffer CSO, 21-1/4 in, 1,000 psi
Tree Storage/ Handling:	90 metric tonnes load rating; 20.3 ft x 19 ft x 78.7 ft
Cranes:	(1) Huisman PMOC 100 T, (1) Huisman PMOC 80 T; (1) Gantry Crane 80 T, (1) Pipe Knuckle Boom Crane 17.5, (2) Pipe Overhead Crane 7.5 T
Mud Pumps:	(4) NOV 14-P-220, 2,200 HP
Engines:	(8) Caterpillar C-280 Tier II Diesel Engines w/4,790 kw per engine
Station Keeping:	DP3
Thrusters:	(6) Rolls Royce 5,000 hp each



Noble Corporation plc
10 Brook Street
London, W1S 1BG
www.noblecorp.com

These specifications are intended for informational purposes only. Noble makes no warranties about the accuracy or completeness of any information contained herein.