

# Noble Johnny Whitstine

## General

Rig Type:	Jackup
Rig Design:	Gusto MSC CJ46
Builder:	PaxOcean
Year Built / Upgraded:	2015 / 2018
Classification:	ABS +A1, Self Elevating Drilling Unit
Flag:	Liberia
MODU Code:	2009



## Ratings & Dimensions

Water Depth:	375 ft
Drilling Depth:	30,000 ft
Length:	214 ft
Breadth:	203 ft
Depth:	26 ft
Leg Length:	503 ft
Leg Spacing:	151 ft / 131 ft
Draft (Operating/ Transit):	15.09 ft
Cantilever Envelope:	75 ft x 20 ft; 2,500 kips
Variable Deck Load:	7,700 kips
Hook Load:	1,500 kips
Setback Capacity:	1,120 kips
Quarters Capacity:	120

## Capacities

Fuel:	4,541 bbls
Drill Water:	22,140 bbls
Liquid Mud:	4,540 bbls
Brine Storage:	1,228 bbls
Base Oil Storage:	1,228 bbls
Bulk Storage:	15,000 cu ft
Sack Storage:	5,000 sacks

## Equipment

Derrick:	NOV Bolted Single Static Bottleneck; 35 ft x 35 ft x 160 ft; 1,500 kips
Racking Capacity:	Pipe capacity, @ DP finger board, 336 Stds 5-1/2 in DP. Casing Capacity @ CSG finger board, 14 Stds 9-1/2 in
Drawworks:	NOV D3000AC
Top Drive:	NOV TDS-8SA; 62,250 ft-lbs @ 270 RPM
Rotary:	NOV D-495; 49-1/2 in
Iron Roughneck:	NOV AR3200M; 100,000 / 120,000 ft-lbs. m/u / - b/o torque
BOP:	NOV NXT-M; 4 ram; 18-3/4 in x 15k psi w/ NOV 18 3/4 in x 10k psi annular
LMRP:	N/A
Control System:	NOV Koomey BOP Control Unit
Pipe Handling System:	Bridge Racker @ 129.5 ft; Range 3-1/2 in - 9-1/2 in; SWL 11 st
Solids Control System:	(5) NOV Brandt King Cobra Hybrid Shakers / 24 cone desilter / 3 cone desander
Diverter:	DrilQuip / NOV 49-1/2"; 500 psi
Cranes:	(3) Favelle Favco API Type-C 55 T
Mud Pumps:	(3) NOV 14-P-220; 2,300 HP
Engines:	(5) CAT 3516 C
Jacking System:	GustoMSC ; 18 pinions per leg



Noble Corporation plc  
10 Brook Street  
London, W1S 1BG  
www.noblecorp.com

These specifications are intended for informational purposes only. Noble makes no warranties about the accuracy or completeness of any information contained herein.