

# Noble Lloyd Noble

## General

Rig Type:	Jackup
Rig Design:	GustoMSC CJ70-X150-ST CAT-J Mariner
Builder:	Jurong Shipyard
Year Built / Upgraded:	2016
Classification:	DNV +1A1 Self Elevating Drilling Unit (N) Additional notations Drill(N), EO, HELDK(SH), CRANE (N), CLEAN DESIGN
Flag:	Liberia
MODU Code:	

## Ratings & Dimensions

Water Depth:	492 ft
Drilling Depth:	32,000 ft
Length:	344 ft
Breadth:	291 ft
Depth:	39 ft
Leg Length:	702 ft
Leg Spacing:	229 ft / 229 ft
Draft (Operating/ Transit):	24 ft transit
Cantilever Envelope:	110 ft x 74 ft (x-y skidding system)
Variable Deck Load:	17,600 kips
Hook Load:	2,000 kips
Setback Capacity:	1,800 kips
Quarters Capacity:	150

## Capacities

Fuel:	10,692 bbls
Drill Water:	17,611 bbls
Liquid Mud:	10,692 bbls
Brine Storage:	3,774 bbls
Base Oil Storage:	3,459 bbls
Bulk Storage:	10,000 cu ft
Sack Storage:	5,000 sacks



## Equipment

Derrick:	NOV capacity 2,000 kips (TBD)
Racking Capacity:	
Drawworks:	NOV SSGD 5750; 5,750HP continuous / 8,050 HP intermittent
Top Drive:	NOV TDX-1000; 67,000 ft-lbs continuous torque
Rotary:	NOV RST; 49-1/2 in
Iron Roughneck:	(2) NOV Hydra Tong ARN270
BOP:	TBD
LMRP:	N/A
Control System:	TBD
Pipe Handling System:	Hydra-Racker IV, X2 dual pipe racker system, pipe catwalk shuttle and pipehandling knuckleboom crane
Solids Control System:	(6) Cubility - mud cube
Diverter:	21-500-49 REG (49 _")
Cranes:	(3) NOV OC 3500 (capacity 187,390 lbs at 65ft)
Mud Pumps:	(3) 14-P-220 Triplex 7,500 psi + (1) 7,500 psi plunger pump (cuttings re-injection)
Engines:	(4) 3,750 kW (TBD)
Jacking System:	Gusto MSC



Noble Corporation plc  
10 Brook Street  
London, W1S 1BG  
www.noblecorp.com

These specifications are intended for informational purposes only. Noble makes no warranties about the accuracy or completeness of any information contained herein.