

Noble Scott Marks

General

Rig Type:	Jackup
Rig Design:	Friede & Goldman JU2000E
Builder:	Dalian Shipyard
Year Built / Upgraded:	2009
Classification:	ABS +A1, Self Elevating Drilling Unit
Flag:	Liberia
MODU Code:	1989



Ratings & Dimensions

Water Depth:	400 ft
Drilling Depth:	30,000 ft
Length:	231 ft
Breadth:	249 ft
Depth:	31 ft
Leg Length:	548 ft
Leg Spacing:	150 ft / 156 ft
Draft (Operating/ Transit):	22 ft
Cantilever Envelope:	75 ft x 30 ft; 2,600 kips
Variable Deck Load:	14,541 kips
Hook Load:	2,000 kips
Setback Capacity:	950 kips
Quarters Capacity:	120

Capacities

Fuel:	4,025 bbls
Drill Water:	9,335 bbls
Liquid Mud:	7,103 bbls
Brine Storage:	1,114 bbls
Base Oil Storage:	1,114 bbls
Bulk Storage:	17,940 cu ft
Sack Storage:	5,000 sacks

Equipment

Derrick:	NOV; 170 ft x 40 ft x 40 ft; c/w Topdrive Parking System
Racking Capacity:	117 stands of 6-5/8 in DP and 104 stands of 5-1/2 in DP and 10 stands of 9-1/2 in DC
Drawworks:	NOV SSGD-750-4600-50-82-10.53
Top Drive:	NOV HPS-750-E-AC-1S-KT; continuous torque 64,175 ft-lbs
Rotary:	NOV D-495; 49-1/2 in Hydraulic Rotary Tablepowered by hydraulic motor with an output of 35,000 ft-lbs
Iron Roughneck:	NOV Hydratong MPT-200; 103,258 / 147512 ft-lbs. m/u / b/o torque
BOP:	Cameron TL; 4 ram; 18-3/4 in x 15k psi w/ Shaffer 18-3/4 in x 10k psi annular
LMRP:	N/A
Control System:	Vetco Grey Type 80
Pipe Handling System:	NOV Hydraracker HR-III-X-Y-SB; 10,000 kg SWL; tubulars up to 13-5/8 in , Pipe handling crane NOV KMCVVT1891 c/w 20 in gripper head
Solids Control System:	(4) Derrick Flo-Line Cleaner 2000/4 panel high (G), 1 x Derrick Flo-Line Cleaner 2000/4 panel High (G) Mud Cleaner
Diverter:	49-1/2 in Vetco KFDJ 500; 500 psi Working Pressure; Max ID 36-1/2 in
Cranes:	(2) NOV 60DNS 120 ft boom, (1) NOV 72DNS 120 ft boom
Mud Pumps:	(3) National 14-P-220; 2,200 HP
Engines:	(5) Caterpillar 3516B-HD
Jacking System:	BLM C150E rack and pinion system rated 1.5 ft per min. 12 pinions per leg.



Noble Corporation plc
10 Brook Street
London, W1S 1BG
www.noblecorp.com

These specifications are intended for informational purposes only. Noble makes no warranties about the accuracy or completeness of any information contained herein.